



The lighted retractor can be attached to a fiber optic light cable with ACMI (female) connector and can be steam sterilized.

PRODUCT NO'S:

6129 [Standard with Sharp Tip]

Overall Length: 12" (30,5 cm)
Handle Length: 7" (17,8 cm)
Blade at Widest: 33 mm

6130 [Standard]

Overall Length: 12" (30,5 cm)
Handle Length: 7" (17,8 cm)
Blade at Widest: 33 mm

6130-L [Lighted Standard]

Overall Length: 12" (30,5 cm)
Handle Length: 7" (17,8 cm)
Blade Width at Widest: 33 mm

6130-R* [OrthoLucent™ Standard]

Overall Length: 12" (30,5 cm)
Handle Length: 7" (17,8 cm)
Blade Width at Widest: 33 mm

6130-01 [Standard with Blunt Teeth]

Overall Length: 12" (30,5 cm)
Handle Length: 7" (17,8 cm)
Blade at Widest: 33 mm

6130-02 [Straight with Blunt Teeth]

Overall Length: 12" (30,5 cm)
Handle Length: 7" (17,8 cm)
Blade at Widest: 33 mm

6132 [Medium]

Overall Length: 12" (30,5 cm)
Handle Length: 7" (17,8 cm)
Blade at Widest: 46 mm

6140 [Wide]

Overall Length: 11.75" (29,8 cm)
Handle Length: 7" (17,8 cm)
Blade at Widest: 56 mm

New!

The OrthoLucent™ version is made of a strong, lightweight carbon fiber PEEK composite material, which is completely radiolucent, helps to prevent from marring component surfaces, and can be steam sterilized.



* MADE EXCLUSIVELY
FOR INNOMED
IN SWITZERLAND

Cobra Retractors

A general purpose instrument for use around the femur and acetabulum

Standard with
Sharp Tip
#6129



Standard
#6130



Lighted Standard
#6130-L



OrthoLucent™
Standard
#6130-R



Standard with
Blunt Teeth
#6130-01



Round and square
tip with additional
teeth on the ends
for better gripping

Straight Tip with
Blunt Teeth
#6130-02



Medium
#6132



Wide
#6140

